

| | |
|---------------------------|---|
| Product Image |  |
| PRODUCT NAME | BULLET |
| PRODUCT CODE | BULLET 25 |
| ENVIRONMENT | INDOOR RECESSED |
| OUTER SIZE (MM) | 105x105x90 |
| CUT OUT SIZE (MM) | 90x90x90 |
| HOUSING | DIE - CAST ALUMINIUM |
| LENS / DIFFUSER | Tempered Glass |
| REFLECTOR | PC High Purity Metallised |
| SURFACE FINISH | WHITE POWDER COATED |
| HEAT SINK MATERIAL | ALUMINIUM |
| COOLING TECHNIQUE | PASSIVE |
| BEAM ANGLE | 24,36 |
| ILLUMINATION MODE | DIRECT LIGHTING |
| SWIVEL | YES |
| LED FITTED | BRIDGELUX |
| LUMINAIRE EFFICACY | 110 LUMENS / WATT |

| | |
|--|---|
| DELIVERED LUMENS | 2750 / 2625 / 2500 |
| CCT (K) | 6000 / 4000 / 3000 |
| CRI (Ra) | 80 |
| LED LIFE | 40,000 HRS |
| UGR | 18 |
| INPUT VOLTAGE | 110 TO 270 V |
| INPUT POWER | 25W |
| POWER FACTOR | >0.95 |
| THD | |
| CONTROL GEAR MOUNTING | REMOTE |
| DRIVER PROTECTION | OVP, Short Circuit, SURGE |
| DIMMING / EMERGENCY KIT /SENSOR | OPTION/AL |
| IP RATING | 20 |
| APPLICATION AREAS | Home, Office buildings, Retail, Sports facilities, Studio, Stage, Supermarkets, library |
| PACKING QTY | |