



## SPECIFICATION SHEET

Product Category : LED SPOT LIGHT

Date: 20-06-2018

Product Image	
PRODUCT NAME	HIPPO
PRODUCT CODE	ADR 30
ENVIRONMENT	INDOOR RECESSED
OUTER SIZE (MM)	160
CUT OUT SIZE (MM)	140x115
HOUSING	DIE - CAST ALUMINIUM
LENS / DIFFUSER	Tempered Glass
REFLECTOR	PC high purity metallised
SURFACE FINISH	IVORY/WHITE POWDER COATED
HEAT SINK MATERIAL	ALUMINIUM
COOLING TECHNIQUE	PASSIVE
BEAM ANGLE	40,60
ILLUMINATION MODE	DIRECT LIGHTING
SWIVEL	YES
LED FITTED	BRIDGELUX
LED FLUX	110 LUMENS / WATT
DELIVERED LUMENS	3120 /3240 /3300
CCT (K)	3000 / 4000 / 6000
CRI (Ra)	90
LED LIFE	30,000 HRS
UGR	18
INPUT VOLTAGE	110 TO 270 V
INPUT POWER	30W
POWER FACTOR	>0.97
THD	
CONTROL GEAR MOUNTING	REMOTE
DRIVER PROTECTION	OVP,Short Circuit,SURGE
DIMMING / EMERGENCY KIT /SENSOR	OPTION/AL
IP RATING	20

**APPLICATION AREAS**

Home,Office buildings,Retail,Sports facilities,Studio, Stage,  
Medical applications,Industrial  
buildings,Supermarkets,Hospitality,library