

AERO SLIM

Product Images

APPLICATION AREAS:

Office

buildings, Retail, Supermarkets, Hospitality, liberar













TECHNICAL SPECIFICATIONS

PRODUCT REFRENCE

ITEM CODE AERO SLIM 15 ENVIRONMENT Indoor

INSTALLATION Suspended

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM 599x73x35

CUT OUT SIZE (MM)

HOUSING Extruded Aluminium **LENS / DIFFUSER High Transmission**

PMMA

REFLECTOR N/A

SURFACE FINISH White/Black/Custom

Powder Coated

30 IP rating

THERMAL MANAGEMENT

HEAT SINK MATERIAL Aluminium **COOLING TECHNIQUE** Passive

OPTICAL SYSTEM

110° **BEAM ANGLE**

ILLUMINATION MODE Direct Lighting

SWIVEL No

LIGHT TECHNOLOGY

LED FITTED Bridgelux

DELIVERED LUMENS 1725 / 1650 / 1575 CCT (K) 6000 / 4000 / 3000

Tunable On Request **LED BINNING** 3 Step MacAdam

CRI (Ra) 80 / 90 **LED LIFE L70** 45.000 HRS

LUMINAIRE 2100 / 2025 / 1950

LUMINOUS FLUX

only fore internal use 140

115 Lumens / Watt **LUMINOUS EFFICACY**

ELECTRICAL SYSTEM

<22 (UGR)

INPUT VOLTAGE 220 TO 240 Vac

INPUT POWER 15W **POWER FACTOR** >0.95 **THD** <10% **CONTROL GEAR** IN BUILT

MOUNTING

DRIVER PROTECTION OVP, Short Circuit, Surge

Phase / Analog / Dali / DIMMING

RF / APP

BACKUP

EMERGENCY BATTERY On Request

PACKAGING DETAILS

PACKING QTY -

GROSS WEIGHT-


CARTOON SIZE -

(LXBXH)

DIMENSIONS



PHOTOMETRIC



ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near dahisar check naka. Mira road 401107

NOTE: The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers