

LED PROFILE

Product Images

APPLICATION AREAS:

Office buildings,Retail,Supermarkets,Hospitality,liberar



TECHNICAL SPECIFICATIONS

ITEM CODE

ENVIRONMENT

INSTALLATION

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM CUT OUT SIZE (MM) HOUSING LENS / DIFFUSER

REFLECTOR SURFACE FINISH

IP rating

1000x23.2X8 1000x17.1X8 Extruded Aluminium High Transmission PMMA N/A Anodised/Custom Powder Coated 20

.....

THERMAL MANAGEMENT

PRODUCT REFRENCE

AR0011708R

Indoor

Recessed

HEAT SINK MATERIAL Aluminium COOLING TECHNIQUE Passive

OPTICAL SYSTEM

BEAM ANGLE110°ILLUMINATION MODEDirect LightingSWIVELNo

LIGHT TECHNOLOGY

LED FITTED	-
DELIVERED LUMENS	-
ССТ (К)	-
Tunable	-
LED BINNING	-
CRI (Ra)	-
LED LIFE L70	-
LUMINAIRE	-
LUMINOUS FLUX	
only fore internal use	-
LUMINOUS EFFICACY	-


(UGR)	-
INPUT VOLTAGE	-
INPUT POWER	-
POWER FACTOR	-
THD	-
CONTROL GEAR	-
MOUNTING	
DRIVER PROTECTION	-
DIMMING	-
EMERGENCY BATTERY	-
BACKUP	

PACKAGING DETAILS


PACKING QTY

GROSS WEIGHT -


CARTOON SIZE -(LXBXH)



-



PHOTOMETRIC



ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near dahisar check naka, Mira road 401107

NOTE : The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

BP-RV00 AR/FRT/TEC/TDS/01