

ARGON UP DOWN

Product Images

APPLICATION AREAS:

Office

buildings, Retail, Supermarkets, Hospitality, liberar













TECHNICAL SPECIFICATIONS

PRODUCT REFRENCE

ITEM CODE ARGON UP DOWN 60

ENVIRONMENT Indoor **INSTALLATION** Suspended

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM 2367x94X80

CUT OUT SIZE (MM)

HOUSING Extruded Aluminium

LENS / DIFFUSER High Transmission

PMMA

REFLECTOR N/A

SURFACE FINISH White/Black/Custom

Powder Coated

30 IP rating

THERMAL MANAGEMENT

HEAT SINK MATERIAL Aluminium **COOLING TECHNIQUE** Passive

OPTICAL SYSTEM

110° **BEAM ANGLE**

ILLUMINATION MODE Direct Lighting

SWIVEL No

LIGHT TECHNOLOGY

LED FITTED Bridgelux

DELIVERED LUMENS 6900 / 6600 / 6300 **CCT (K)** 6000 / 4000 / 3000

Tunable On Request **LED BINNING** 3 Step MacAdam

CRI (Ra) 80 / 90 **LED LIFE L70** 45.000 HRS

LUMINAIRE 8400 / 8100 / 7800

LUMINOUS FLUX

only fore internal use 140

LUMINOUS EFFICACY 115 Lumens / Watt

ELECTRICAL SYSTEM

(UGR) <22

 INPUT VOLTAGE
 220 TO 240 Vac

 INPUT POWER
 60W (20U+40D)

POWER FACTOR >0.95
THD <10%
CONTROL GEAR IN BUILT

MOUNTING

DRIVER PROTECTION OVP,Short Circuit,Surge

DIMMING Phase / Analog / Dali /

RF / APP

EMERGENCY BATTERY On Request


BACKUP

PACKAGING DETAILS


PACKING QTY - GROSS WEIGHT - CARTOON SIZE -

(LXBXH)

DIMENSIONS



PHOTOMETRIC



ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near dahisar check naka, Mira road 401107

NOTE: The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers