

HEXA SLIM

Product Images

APPLICATION AREAS:

Office
buildings, Retail, Supermarkets, Hospitality, Libera



LUMENS
PER WATT
CW - 100
NW - 98
WW - 93

CCT Tuning

Burning Hours
45K

RF Control

Low Glare

TECHNICAL SPECIFICATIONS

PRODUCT REFERENCE

ITEM CODE HEXA SLIM 25 450
ENVIRONMENT Indoor
INSTALLATION Suspended

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM 450 Dia x 60
CUT OUT SIZE (MM) -
HOUSING Extruded Aluminium
LENS / DIFFUSER High Transmission PMMA
REFLECTOR N/A
SURFACE FINISH White/Black/Custom Powder Coated
IP rating 30

THERMAL MANAGEMENT

HEAT SINK MATERIAL Aluminium
COOLING TECHNIQUE Passive

OPTICAL SYSTEM

BEAM ANGLE 110°
ILLUMINATION MODE Direct Lighting
SWIVEL No

LIGHT TECHNOLOGY

LED FITTED	Bridgelux
DELIVERED LUMENS	2500 / 2375 / 2250
CCT (K)	6000 / 4000 / 3000
Tunable	On Request
LED BINNING	3 Step MacAdam
CRI (Ra)	80 / 90
LED LIFE L70	45,000 HRS
LUMINAIRE	3500 / 3375 / 3250
LUMINOUS FLUX	
only fore internal use	140
LUMINOUS EFFICACY	100 Lumens / Watt

ELECTRICAL SYSTEM

(UGR)	<22
INPUT VOLTAGE	220 TO 240 Vac
INPUT POWER	25W
POWER FACTOR	>0.95
THD	<10%
CONTROL GEAR	Remote
MOUNTING	
DRIVER PROTECTION	OVP, Short Circuit, Surge
DIMMING	Phase / Analog / Dali / RF / APP
EMERGENCY BATTERY BACKUP	On Request


PACKAGING DETAILS

PACKING QTY 2

GROSS WEIGHT -

CARTOON SIZE 20"x20"x7.5"
(LXBXH)

DIMENSIONS



PHOTOMETRIC



ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near
dahisar check naka, Mira road 401107

NOTE : The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

Technical parameters are subjected to change time to time in order to improve product performance and reliability
BP-RV00 AR/FRT/TEC/TDS/01

