

IYON RECESS

Product Images

APPLICATION AREAS:

Office
buildings, Retail, Supermarkets, Hospitality, liberal



TECHNICAL SPECIFICATIONS

PRODUCT REFERENCE

ITEM CODE	IYON RECESS 36
ENVIRONMENT	Indoor
INSTALLATION	Recessed

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM	1099x47x46
CUT OUT SIZE (MM)	1085x37x46
HOUSING	Extruded Aluminium
LENS / DIFFUSER	High Transmission PC Lens
REFLECTOR	PC High Purity Metallised
SURFACE FINISH	White/Black/Custom Powder Coated
IP rating	30

THERMAL MANAGEMENT

HEAT SINK MATERIAL	Aluminium
COOLING TECHNIQUE	Passive

OPTICAL SYSTEM



BEAM ANGLE	60°
ILLUMINATION MODE	Direct Lighting
SWIVEL	No

LIGHT TECHNOLOGY

LED FITTED	Bridgelux, Osram, Cree
DELIVERED LUMENS	4500 / 4320 / 4140
CCT (K)	6000 / 4000 / 3000
Tunable	On Request
LED BINNING	3 Step MacAdam
CRI (Ra)	80 / 90
LED LIFE L70	45,000 HRS
LUMINAIRE	5040 / 4860 / 4680
LUMINOUS FLUX	
only fore internal use	140
LUMINOUS EFFICACY	125 Lumens / Watt

ELECTRICAL SYSTEM

(UGR)	<9
INPUT VOLTAGE	220 TO 240 Vac
INPUT POWER	36W
POWER FACTOR	>0.96
THD	<10%
CONTROL GEAR	Remote
MOUNTING	
DRIVER PROTECTION	OVP, Short Circuit, Surge
DIMMING	Phase / Analog / Dali / RF / APP
EMERGENCY BATTERY BACKUP	On Request

PACKAGING DETAILS**PACKING QTY** 2**GROSS WEIGHT** -**CARTON SIZE** -
(LXBXH)**DIMENSIONS****PHOTOMETRIC****ARCADE LIGHTING INDUSTRIES PVT LTD**

8 Raju industrial estate, Penkar pada, Near
dahisar check naka, Mira road 401107

NOTE : The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

Technical parameters are subjected to change time to time in order to improve product performance and reliability
BP-RV00 AR/FRT/TEC/TDS/01