

LASER LINE RECESS

Product Images

APPLICATION AREAS:

Office buildings,Retail,Supermarkets,Hospitality,liberar



TECHNICAL SPECIFICATIONS

ITEM CODE

ENVIRONMENT

INSTALLATION

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM
CUT OUT SIZE (MM)
HOUSING
LENS / DIFFUSER

2406x47x46 2398x37x46 Extruded Aluminium High Transmission PC Lens PC High Purity Metallised White/Black/Custom Powder Coated 30

REFLECTOR

SURFACE FINISH

IP rating

THERMAL MANAGEMENT

PRODUCT REFRENCE

Indoor

Recessed

HEAT SINK MATERIAL Aluminium COOLING TECHNIQUE Passive

OPTICAL SYSTEM

BEAM ANGLE24°,40°ILLUMINATION MODEDirect LightingSWIVELNo

Technical parameters are subjected to change time to time in order to improve product performance and reliability

LASER LINE RECESS 60

LIGHT TECHNOLOGY

LED FITTEDBridDELIVERED LUMENS750CCT (K)600TunableOn FLED BINNING3 StCRI (Ra)80 /LED LIFE L7045,0LUMINAIRE8400LUMINOUS FLUX140LUMINOUS EFFICACY125

Bridgelux,Osram,Cree 7500 / 7200 / 6900 6000 / 4000 / 3000 On Request 3 Step MacAdam 80 / 90 45,000 HRS 8400 / 8100 / 7800 140 125 Lumens / Watt

DIMENSIONS

ELECTRICAL SYSTEM

(UGR) INPUT VOLTAGE INPUT POWER POWER FACTOR THD CONTROL GEAR MOUNTING DRIVER PROTECTION DIMMING <16 220 TO 240 Vac 60W >0.95 <10% Remote

OVP,Short Circuit,Surge Phase / Analog / Dali / RF / APP On Request

EMERGENCY BATTERY On Request BACKUP


PACKAGING DETAILS

PACKING QTY 2


GROSS WEIGHT -

CARTOON SIZE 96"x 5.2"x 4.2" (LXBXH)

PS.



PHOTOMETRIC



ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near dahisar check naka, Mira road 401107

NOTE : The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

Technical parameters are subjected to change time to time in order to improve product performance and reliability BP-RV00 AR/FRT/TEC/TDS/01