

LED STRIP (NON FLEXIBLE) APPLICATION AREAS:

Product Images

Office buildings, Retail, Supermarkets, Hospitality, liberar



TECHNICAL SPECIFICATIONS

CONSTRUCTION AND MATERIALS

PRODUCT REFRENCE

ITEM CODE

ENVIRONMENT INSTALLATION LED STRIP DUO 2835 120 Indoor -

SIZE OUT SIDE MM CUT OUT SIZE (MM) HOUSING LENS / DIFFUSER

REFLECTOR SURFACE FINISH

IP rating

1000x18x17 --High Transmission PMMA N/A White/Black/Custom Powder Coated 20

Linkable Smart Lighting CCT Tuning

THERMAL MANAGEMENT

HEAT SINK MATERIAL Aluminium COOLING TECHNIQUE Passive

OPTICAL SYSTEM

BEAM ANGLE120°ILLUMINATION MODEDirect LightingSWIVELNo

LIGHT TECHNOLOGY

ELECTRICAL SYSTEM

LED FITTED	Bridgelux	(UGR)	<22
DELIVERED LUMENS	1500 / 1425 / 1350	INPUT VOLTAGE	220 TO 240 Vac
CCT (K)	6000 / 4000 / 3000	INPUT POWER	15W
Tunable	On Request	POWER FACTOR	>0.95
LED BINNING	3 Step MacAdam	THD	<10%
CRI (Ra)	80 / 90	CONTROL GEAR	Remote
LED LIFE L70 LUMINAIRE LUMINOUS FLUX only fore internal use LUMINOUS EFFICACY	45,000 HRS 2100 / 2025 / 1950 140 100 Lumens / Watt	MOUNTING DRIVER PROTECTION DIMMING EMERGENCY BATTERY BACKUP	OVP,Short Circuit,Surge Phase / Analog / Dali / RF / APP On Request


PACKAGING DETAILS


PACKING QTY -

GROSS WEIGHT -


CARTOON SIZE - (LXBXH)

DIMENSIONS





PHOTOMETRIC



ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near dahisar check naka, Mira road 401107

NOTE : The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

Technical parameters are subjected to change time to time in order to improve product performance and reliability BP-RV00 AR/FRT/TEC/TDS/01