

MOON SURFACE

Product Images

APPLICATION AREAS:

Office

buildings, Retail, Supermarkets, Hospitality, Libera













TECHNICAL SPECIFICATIONS

PRODUCT REFRENCE

ITEM CODE MOON SURFACE 36 600

ENVIRONMENT Indoor **INSTALLATION** Surface

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM 600x90

CUT OUT SIZE (MM)

HOUSING Extruded Aluminium
LENS / DIFFUSER High Transmission

 PMMA

REFLECTOR N/A

SURFACE FINISH White/Black/Custom

Powder Coated

IP rating 30

THERMAL MANAGEMENT

HEAT SINK MATERIAL Aluminium COOLING TECHNIQUE Passive

OPTICAL SYSTEM

BEAM ANGLE 110°

ILLUMINATION MODE Direct Lighting

SWIVEL NO

No

LIGHT TECHNOLOGY

LED FITTED Bridgelux

DELIVERED LUMENS 3600 / 3420 / 3240 **CCT (K)** 6000 / 4000 / 3000

Tunable On Request **LED BINNING** 3 Step MacAdam

CRI (Ra) 80 / 90 **LED LIFE L70** 45,000 HRS

LUMINAIRE 5040 / 4860 / 4680

LUMINOUS FLUX

only fore internal use 140

LUMINOUS EFFICACY 100 Lumens / Watt

ELECTRICAL SYSTEM

(UGR) <22

INPUT VOLTAGE 220 TO 240 Vac

INPUT POWER 36W
POWER FACTOR >0.95
THD <10%
CONTROL GEAR IN BUILT

MOUNTING

DRIVER PROTECTION OVP,Short Circuit,Surge

DIMMING Phase / Analog / Dali /

RF / APP

EMERGENCY BATTERY On Request


BACKUP

PACKAGING DETAILS

PACKING QTY - GROSS WEIGHT - CARTOON SIZE - (LXBXH)

DIMENSIONS

PHOTOMETRIC



ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near dahisar check naka, Mira road 401107

NOTE: The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

Technical parameters are subjected to change time to time in order to improve product performance and reliability BP-RV00 AR/FRT/TEC/TDS/01