

TURBO SUSPENDED

Product Images

APPLICATION AREAS:

Home,Office buildings,Retail,Sports facilities,Studio, Stage,Supermarkets,liberary













TECHNICAL SPECIFICATIONS

PRODUCT REFRENCE

ITEM CODE TURBO SUSPENDED 20
ENVIRONMENT Indoor

INSTALLATION Suspended

CONSTRUCTION AND MATERIALS

SIZE OUT SIDE MM 85 Dia x 140

CUT OUT SIZE (MM) -

HOUSING Extruded Aluminium **LENS / DIFFUSER** High Transmission PC

REFLECTOR PC High Purity Metallised

SURFACE FINISH White/Black/Custom

Powder Coated

IP rating 20

THERMAL MANAGEMENT

HEAT SINK MATERIAL Aluminium COOLING TECHNIQUE Passive

OPTICAL SYSTEM

BEAM ANGLE 24°,36°,60° **ILLUMINATION MODE** Direct Lighting **SWIVEL** No

....

LIGHT TECHNOLOGY

LED FITTED Bridgelux

DELIVERED LUMENS 2300 / 2200 / 2100 **CCT (K)** 6000 / 4000 / 3000

Tunable On Request **LED BINNING** 3 Step MacAdam

CRI (Ra) 80 / 90 **LED LIFE L70** 40,000 HRS

LUMINAIRE 3200 / 3100 / 3000

LUMINOUS FLUX

only fore internal use 160

LUMINOUS EFFICACY 115 Lumens / Watt

ELECTRICAL SYSTEM

(UGR) <19

INPUT VOLTAGE 220 TO 240 Vac

INPUT POWER 20W
POWER FACTOR >0.95
THD <10%
CONTROL GEAR IN BUILT

MOUNTING

DRIVER PROTECTION OVP,Short Circuit,Surge

DIMMING Phase / Analog / Dali /

RF / APP

EMERGENCY On Request

BATTERY BACKUP


PACKAGING DETAILS


PACKING QTY - GROSS WEIGHT- CARTOON SIZE -

(LXBXH)

DIMENSIONS

PHOTOMETRIC





ARCADE LIGHTING INDUSTRIES PVT LTD

8 Raju industrial estate, Penkar pada, Near dahisar check naka, Mira road 401107

NOTE: The technical data sheet with design registration stamp is the property of Arcade Lighting India Pvt. Ltd. & protected under Intellectual Property law, and it is restricted for sharing with other lighting suppliers

Technical parameters are subjected to change time to time in order to improve product performance and reliability BP-RV00 AR/FRT/TEC/TDS/01